



# The Mohawk Group

Commercial VCT Flooring

<b>Product:</b>	<b>ALTERNATIVES</b>
<b>Construction:</b>	Vinyl Composition (Polish required)
<b>Gauge (nominal):</b>	0.125" (1/8") (3.2mm)
<b>Size:</b>	12" X 12"
<b>Packaging:</b>	45 S.F./carton
<b>Shipping Weight per Package:</b>	64lbs./carton
<b>Passes NBS Smoke Density:</b>	Yes
<b>Passes Critical Radiant Flux (ASTM E-648 &gt; 0.45w/cm<sup>2</sup>):</b>	Yes
<b>Static Load Limit:</b>	250 psi
<b>Applic. Fed. Specifications:</b>	ASTM F 1066, Cl. 2, Comp. 1 MIL STD-1 623 D for Deck Covering
<b>Warranty Coverage:</b>	Two Star (Residential) Five Year (Commercial)
<b>Installation Method:</b>	Full spread
<b>Subfloor Application:</b>	On, above, or below grade level
<b>Adhesive:</b>	AD-42 Clear Thin-Spread
<b>Suggested Usage:</b>	
<b>Public Commercial</b>	Excellent
<b>Light Commercial</b>	Excellent
<b>Private Residential</b>	Good

*Congoleum*<sup>®</sup>