






54004 Merlot Cherry




54201
Natural Chestnut




52710
Warm Honey Oak



52715
Sorrel Oak




54101
Heathered Walnut




54208
Molasses Chestnut




52711
Auburn Oak




54203
Tawny Chestnut



52713
Cinnamon Oak




54003
Sunset Amendoim




54004
Merlot Cherry




53901
Java Teak



53902
Driftwood Teak



54205
Chocolate Chestnut



54104
Toasted Walnut

DESIGN

Product Type Floating Resilient Tile
 Overall Gauge 0.16" (4mm)
 Wear Layer 12 mil (0.3mm)
 Finish Commercial Grade Urethane
 Colors Available 14
 Size 5.9" x 49" (149.9mm x 1244.6mm)
 Packaging 28.17 sf/ctn (2.62 m²/ctn); 14 pcs/ctn;
 47.41 lbs/ctn (21.50 kg/ctn)
 Installation Floating with Uniclic® Locking System
 Recommended Adhesive None required

SELLING FEATURES

- Uniclic® locking system keeps planks tightly in place, saving adhesive costs
- Installs quickly and is move in ready
- Wood textures emulate natural materials
- No-polish maintenance reduces occupied costs

PERFORMANCE

Construction Commercial Grade Floating Resilient Tile
 Classification ASTM F1700 - Class III, Type A - Smooth,
 Type B - Embossed
 Squareness ASTM F2055 - Passes - 0.010 in. max
 Size and Tolerance ASTM F2055 - Passes - ±0.016 in. per linear foot
 Thickness ASTM F386 - Passes- as specified ±0.005 in (±0.13 mm)
 Flexibility ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
 Dimensional Stability ASTM F2199 - Passes - 0.15% max
 Static Load Limit ASTM F970 - Passes - Exceeds 250 psi
 Residual Indentation ASTM F1914 - Passes - Average less than 8%
 Slip Resistance ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry
 Resistance to Chemicals ASTM F925 - Passes - No Change
 Resistance to Light ASTM F1515 - Passes - ΔE ≤ 8
 Resistance to Heat ASTM F1514 - Passes - ΔE ≤ 8
 Critical Radiant Flux ASTM E648 - Passes - ≥ 0.45 watts/cm², Class 1
 Smoke Density ASTM E662 - Passes - < 450

SUSTAINABILITY

Certification FloorScore® Certified

SERVICE

Warranties Limited 6 Year Commercial