

**Name** FLEXLOK  
**Product ID** Flexlok Modular Carpet Tabs  
**Website** www.mohawkgroup.com

**Classification** 01 73 19.00 General  
Requirements: Installation



**Manufacturer Address** Mohawk Group  
160 South Industrial Blvd.  
Calhoun, Ga. 30701

**Contact Name** Rochelle Routman  
**Title** Director of Sustainability,  
Commercial Flooring  
**Phone** 706-624-2193  
**Email** rochelle\_routman@mohawkind.com

**Description** Flexlok is a fuss-free, fume-free, fast and flexible adhesive tab for installing modular carpet. They're odorless, non-toxic, efficient to apply and easily removed. They'll work on any substrate, including wood, VCT and concrete. The environmentally-friendly Flexlok system is CRI Green Label-certified and virtually eliminates VOCs. And since it will never dry out like wet adhesives, Flexlok lets you install your floors at your own pace.

**Release Date** 2014-04-18  
**Expiry Date** 2017-04-18  
**HPD URL** <http://tool.hpdcollaborative.org/uploads/files/hpds/18/735-20140418220011.pdf>

Self-declared  
 Second Party  
 Third Party  
**Certifier**  
**Certificate #**

## SUMMARY DISCLOSURE

The content of this product was assessed for health hazard warnings as required using Pharos

### Residuals Disclosure

- Measured 100 ppm (ideal)
- Measured 1000 ppm
- Predicted by process chemistry
- As per MSDS (1,000 & 10,000 ppm)
- Not disclosed
- Other

### Full Disclosure of Intentional Ingredients

Yes  No

### Full Disclosure of Known Hazards

Yes  No

### Disclosure Notes

## Contents in Descending Order of Quantity

VINYL ACETATE, POLYMER WITH N-BUTYL ACRYLATE, POLYETHYLENE, RAYON, WATER

### Hazards

- PBT (Persistent Bioaccumulative Toxic)
- Cancer
- Gene Mutation
- Development
- Reproductive
- Endocrine
- Respiratory

### Highest concern GreenScreen score - List Translator Unspecified

- Neurotoxicity
- Mammal
- Skin or Eye
- Aquatic toxicity
- Land toxicity
- Physical hazard
- Global warming
- Ozone depletion
- Multiple
- Unknown

### Total VOC Content

**Material (g/L)** N/A

**Regulatory (g/L)** N/A

**Does the product contain exempt VOCs?**

N/A  Yes  No

**Are there VOC-free tints available?**

N/A  Yes  No

### Notes

## Certifications + Compliance

**VOC Emissions** CRI Green Label Plus - Adhesives

**VOC Content** N/A

The HPD Standard is solely a declaration of product content and direct health hazards associated with exposure to its individual contents. It is not a full assessment of environmental impacts from the life cycle of this product. It is not an assessment of risks associated with actual use of the product. It does not address the potential health impacts of substances used or created during manufacture that do not appear in the final product as residuals, nor substances created during combustion or other degradation processes.

This Health Product Declaration was generated following the requirements of the noted Standard version and is valid for a total of three years after date of issue or three months after a substantive change of product contents occurs. Users should verify that this Health Product Declaration is compliant with the most current version of the HPD Standard. Accuracy of claims made in this Health Product Declaration is the sole responsibility of the listed manufacturer and certifier (if applicable). The HPD Collaborative does not warrant any claim made herein, explicit or implicit. The HPD Standard is an “open standard” developed and managed by the HPD Collaborative, a nonprofit organization. For more information, visit [hpdcollaborative.org](http://hpdcollaborative.org).

## CONTENT IN DESCENDING ORDER OF QUANTITY

All ingredients must be assessed for health warnings against Priority Hazard Lists, regardless of disclosure level.

Priority Hazard Lists and information on the GreenScreen Benchmarks can be found at [www.hpdcollaborative.org/hazardlists](http://www.hpdcollaborative.org/hazardlists).

**GS:** GreenScreen Benchmark; **RC:** Recycled Content, **PC:** Post Consumer, **PI:** Post Industrial (Pre-consumer), **BO:** Both; **Nano:** comprised of nanoscale particles or nanotechnology

Name	CAS RN	% weight	GS	RC	Nano	Role
Hazard A	Warning A					
Hazard B	Warning B					
Hazard C	Warning C					
Hazard D	Warning D					
Hazard E	Warning E					
Notes						
<b>VINYL ACETATE, POLYMER WITH N-BUTYL ACRYLATE</b>	25067-01-0	25 - 35 %	LT-U	N	N	Acrylic Adhesive Polymer
None found	No warnings found on HPD Priority lists					
<b>POLYETHYLENE</b>	9002-88-4	25 - 35 %	LT-U	N	N	Carrier
None found	No warnings found on HPD Priority lists					
<b>RAYON</b>	99331-82-5	12 - 22 %		N	N	Scrim
None found	No warnings found on HPD Priority lists					
<b>WATER</b>	7732-18-5	0 - 8 %		N	N	Moisture Bound in Adhesive
None found	No warnings found on HPD Priority lists					

## CERTIFICATIONS AND COMPLIANCE

**Certifying Party** = First: Manufacturer’s self-declaration; Second: Verification by trade association or other interested party; Third: Verification by independent certifier (ideal).

**Applicable facilities** = Manufacturing sites to which testing applies.

Type	Standard or Certification			Certifier or Laboratory
	Certifying Party	Issue	Expiry	Certificate URL

		Date	Date	
	<b>Applicable Facilities</b>			
	<b>Notes</b>			
VOC Emissions	CRI Green Label Plus - Adhesives		Carpet & Rug Institute (CRI)	
	2nd party industry based certification	2013-12-31	2014-12-31	<a href="http://tool.hpdcollaborative.org/uploads/files/certifications/18/1394396642.pdf">http://tool.hpdcollaborative.org/uploads/files/certifications/18/1394396642.pdf</a>
	All facilities			
	Flexlok is an installation system for Modular Carpet			
VOC Content	N/A			
Recycled Content	Not tested			
Other				

**ACCESSORY MATERIALS**

This section is for additional products required by warranty or recommended by the manufacturer for installation (such as adhesives, fasteners, or factory coatings) or for maintenance, cleaning, or operations. Refer to Health Product Declarations, published separately, for a complete view of these products. Note: This declaration is not intended to address hazards of the installation process.

Required or Recommended Product	URL for Companion Health Product Declaration
<b>Condition when required or recommended and/or other notes</b>	

**NOTES**

The Flexlok installation system will install 110-150 square yards of modular tiles as a flexible floating floor. No application of adhesive is required to the subfloor. The system has lower VOC's for better indoor air quality, and is certified in the Carpet and Rug Institutes Green Label Plus program for adhesives.